



Cordless Belt Sander DBS180

High power BL motor provides excellent performance similar to corded tool.









Work efficiency as high as a corded tool





Connectable to vacuum cleaners

Accessories *Standard Equipment



Dust cover complete (option) increasing dust

extraction rate

A-34590

A-34609

Movable LED job light



LED job light is manually angle-adjustable to match the angle of the sanding arm or the shape of the workpiece.

Part No.

125157-7

*125158-5

125159-3

Part No.

192278-0

192279-8

Variable speed control dial



provides versatility for use on both wood and steel materials.

Dust nozzle assembly

Part No. 122652-8

Part No. 193618-5

Stand set

Electric brake

Dust cover complete

Part No. 191N60-8

Part No. 192349-3

Joint 25

minimizes down-time between sandings by quickly stopping the belt.



A-34475

A-34481



A-34540

A-34556

100

120

TIBV Date HUMHTON	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 _{min}	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Belt Sander

DBS180 9 mm x 533 mm (3/8"x 21")

Size

1.5 m

3.0 m

Marke Brake	Belt Width	6 / 9 / 13 mm (1/4 / 3/8 / 1/2")	
U Brance	Belt Length	533 mm (21")	
Variable Speed	Belt Speed	600 - 1,700 m/min	
	Vibration Level	2.5 m/s ² or less	
Here The Provident Provident Provident Provident Provident Provident Provident Providence Providenc	Sound Pressure Level	77 dB(A)	
	Dimensions (L x W x H)	w/BL1830B/BL1840B/BL1850B/BL1860B: 500x96x116 mm	
		(19-3/4"x3-3/4"x4-9/16")	
N Bane mood Eight		w/ Side Grip / BL1860B: 500x245x126 mm (19-3/4x9-5/8x5")	
	Net weight	1.8 - 2.1 kg (4.0 - 4.6 lbs.)	

Standard Equipment : Sanding Belt, Grip, Grip Base, Battery, Charger

Weight, with battery cartridge, according to EPTA-Procedure 01/2014 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan