



Satisfy Professional's Needs

# Cordless Hammer Driver Drill **LXT** Cordless Driver Drill

**DHP486** 13 mm (1/2") / **DDF486** 13 mm (1/2")



**Compact  
But high power**

**18V  
LITHIUM-ION**

Max Lock Torque

**125 N·m**

**BL MOTOR XPT**

# Increased performance in continuous heavy-duty applications

## Compact design

On top of the higher performance in continuous heavy-duty applications compared with the current model, shorter overall length is achieved by optimizing the design of the gear assembly.



**All metal gear construction**  
for extra-high transmission durability



Mechanical 2-speed transmission



## Max clutch torque: 12 N·m

Due to the increased contact area of the clutch cam, the max clutch torque is increased, enabling to tighten a heavy-duty fastener such as a dia. 9.0x50mm lag bolt in screwdriving mode.

## Hi-speed Max. 2,100 RPM

## High power

**BL MOTOR**



Twin LED job light with preglow and afterglow functions



Variable speed control trigger

## Cordless Hammer Driver Drill DHP486



## Cordless Driver Drill DDF486



Belt clip

**XPT**  
EXTREME PROTECTION TECHNOLOGY

Cordless Hammer Driver Drill	DHP486 13 mm (1/2")	
Cordless Driver Drill	DDF486 13 mm (1/2")	
Variable Speed	<b>Capacity</b>	<b>DHP486</b>
Brake	Steel: 13 mm (1/2")	<b>DDF486</b>
Reversing	Wood (Auger-Bit): 50 mm (2")	Steel: 13 mm (1/2")
Mechanical 2-Speed	Wood (Self-Feed Bit): 76 mm (3")	Wood (Auger-Bit): 50 mm (2")
Keyless Chuck	Wood (Hole Saw): 152 mm (6")	Wood (Self-Feed Bit): 76 mm (3")
Torque Setting 21	Masonry: 16 mm (5/8")	Wood (Hole Saw): 152 mm (6")
Built-in Job Light	Siding Board: 170 mm (6-11/16")	-
Carrying Case	178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")	Siding Board: 170 mm (6-11/16")
		1.5 - 13 mm (1/16 - 1/2")
		-
	<b>Chuck Capacity</b>	High / Low: 0 - 2,100 / 0 - 550
	<b>Impacts Per Minute (IPM)</b>	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
	<b>No Load Speed (RPM)</b>	125 N·m (1,100 in.lbs.)
	<b>Max Fastening Torque</b>	High / Low: 0 - 2,100 / 0 - 550
	<b>Max Lock Torque</b>	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
	<b>Dimensions (L x W x H)</b>	125 N·m (1,100 in.lbs.)
	w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")	w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")
	w/ BL1830B / BL1840B / BL1850B / BL1860B:	w/ BL1830B / BL1840B / BL1850B / BL1860B:
	178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")	178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")
	<b>Net weight</b>	2.3 - 2.6 kg (5.1 - 6.0 lbs.)
		2.3 - 2.6 kg (5.1 - 5.7 lbs.)

**Standard Equipment:** Depth Gauge(DHP486 only), Side Handle, Belt Clip, (+)(-) Bit, Bit Holder, Charger, Battery

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202012