



1.6mm (16Ga)

Cordless Nibbler

BJN161 / BJN160



Satisfy Professional's Needs



**Cordless provides
smooth operation**

Photo : BJN161

Excellent performance as powerful as AC model

Easy-to-operate slide-type on/off switch with lock-on function

Grooves in die holder serve as thickness gauge for allowable cutting thickness:
1.2mm (18Ga.)
1.6mm (16Ga.)

Die holder swivels a full 360 according to shape of material and cutting direction, and is positively locked at 90 each.

Notch in die holder indicates the cutting line on material.

Chip Disposal: Chips fall below, not remaining on material, where they can cause rust. No burrs on surface.

Externally accessible carbon brush

Easy-to-grip motor housing

- Small circumference for easy handling
- Rubberized soft grip for more comfort and better control with minimized hand fatigue and pain.

Battery capacity warning lamp

When remaining battery capacity decreases below a certain limit, the motor automatically stops and solid red light reminds you to replace battery.

Anti-restart function for safety (with warning lamp)

The motor does not start up if battery is inserted with the switch locked on. In this case, the lamp starts blinking slowly, indicating that the Anti-restart function is on; and can be turned off by sliding the switch to the off position.

Warning lamp

High cutting capacity

- up to **1.6mm (16Ga)** thick mild steel
- up to **1.2mm (18Ga)** thick stainless steel
- up to **2.5mm (12Ga)** thick aluminum

Battery

Model: BJN161



BL1830:
18V 3.0Ah

Model: BJN160



BL1430:
14.4V 3.0Ah

Charger

DC18RC / DC18RA
Charging time
22minutes



Fast
Charging
22
min



DC18SD
Charging time
60minutes



Punch

Part No. A-83951



Die

Part No. A-15051



Cordless Nibbler BJN161 / BJN160 1.6mm (16Ga)

	BJN161	BJN160
Capacity	Steel up to 400 N/mm ² : 1.6mm (16Ga) Steel up to 600 N/mm ² : 1.2mm (18Ga) Aluminum up to 200 N/mm ² : 2.5mm (12Ga)	Steel up to 400 N/mm ² : 1.6mm (16Ga) Steel up to 600 N/mm ² : 1.2mm (18Ga) Aluminum up to 200 N/mm ² : 2.5mm (12Ga)
Min. cutting radius	Outside edge : 50mm (2") Inside edge : 45mm (1-3/4")	Outside edge : 50mm (2") Inside edge : 45mm (1-3/4")
Strokes per minute (spm)	1,900	1,900
Dimensions (L x W x H)	313x78x189mm (12-3/8"x3-1/16"x7-7/16")	313x78x174mm (12-3/8"x3-1/16"x6-7/8")
Net Weight*	2.2kg (4.8lbs) with BL1830	2.1kg (4.6lbs) with BL1430
Carrying Case		

Standard Equipment : Hex Wrench, Wrench, Punch, Die

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BC-BA