

Compact and highly efficient high maneuverability and long run time













Shortened head length

for increased maneuverability



High/Low 2-speed selection with variable speed in each range

enables to adjust the speed setting to match user's needs.

1: Low (for polishing) 0 - 2,800 min⁻¹ 2: High (for sanding) 0 - 9,500 min⁻¹















Pad 50

Adapter

Fiber sanding disc and Surface conditioning disc



Accessories For polishing work

Pad 75 Diameter: 75mm Easy to change Hook & Loop style Part No. 743125-4 Sponge pad and Wool pad



Diameter: 80mm For applying wax, removing wax and polishing

Shape	Part No.	Shape	Part No.
	191N90-9		191N91-7

Wool pad 80mm

Diameter: 80mm For surface treatment



For sanding work

Pad 50

Diameter: 46mm Twist-on/twist-off style applicable to heavy-duty operation

Part No. 743124-6







Diameter: 50mm, Twist-on/twist-off type, 25pcs/set For Material: Metal / Stainless, Aluminum

Surface conditioning disc

Туре	Application		Part No.
Hard	• Surface polishing • Removing paint/rust	Coarse	E-07462
		Medium	E-07478
		Fine	E-07484
Soft	Surface polishing	Medium	E-07490
		Fine	E-07509
		Very fine	E-07515



Diameter: 50mm, Twist-on/twist-off type, 25pcs/set For Material: Metal / Stainless, Aluminum

Grit	Application	Part No.
A60	• Grinding • Chamfer • Deburring • Surface polishing	E-07412
A80		E-07428
A120		E-07434
Z60	• Grinding • Chamfer • Deburring	E-07440
Z80		E-07456

Cordless Sander Polisher



Variable Speed



Mechanical 2-Speed





Standard Equipment:

Side Grip, Pad, Adapter, Wool Pad, Sponge Pad, Battery, Charger

PV301D/ DPV300

Pad / Disc Diameter Backing Pad Diameter No Load Speed (RPM)

Continuous Use (min.) Head Length Vibration Level Sound Pressure Level Dimensions (L x W x H)

Net weight

Twist-On / Twist-Off Style: 50 mm (2") Hook & Loop Style: 80 mm (3-1/8") Twist-On / Twist-Off Style: 75 mm (2-15/16") Hook & Loop Style: 46 mm (1-13/16") Polishing: 0 - 2,800, Sanding: 0 - 9,500 w/BL1041B: 18 127 mm (5") Disc Sanding, Polishing: 2.5 m/s² or less 73 dR(A)

w/o Battery: 133 x 67 x 201 mm (5-1/4 x 2-5/8 x 7-7/8") w/BL1016/BL1021B: 137 x 67 x 231 mm (5-3/8 x 2-5/8 x 9-1/8") w/RI 1041R

139 x 67 x 249 mm (5-1/2 x 2-5/8 x 9-3/4") 1.1 - 1.2 kg (2.4 - 2.6 lbs.)

DPV300

Twist-On / Twist-Off Style: 50 mm (2") Hook & Loop Style: 80 mm (3-1/8") Twist-On / Twist-Off Style: 75 mm (2-15/16") Hook & Loop Style: 46 mm (1-13/16") Polishing: 0 - 2,800, Sanding: 0 - 9,500

127 mm (5")

Disc Sanding, Polishing: 2.5 m/s² or less 73 dR(A) 73 Up(n) w/o Battery: 152 x 79 x 205 mm (6 x 3-1/8 x 8-1/8") w/ BL 1818N / BL 1820B: 159 x 79 x 240 mm (6-1/4 x 3-1/8 x 9-1/2")

w/BL1830B / BL1840B / BL1850B / BL1860B: 160 x 79 x 256 mm (6-5/16 x 3-1/8 x 10-1/8") 1.3 - 1.6 kg (2.9 - 3.5 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation