Satisfy Professional's Needs



Cordless Drywall Sander DSL801 225 mm (8-7/8")

Less dust, **More comfort**

Dust collection rate

95% Test conditions: - Operation: 30 second continuous grinding with a constant load - Grit of Abrasive paper disc: #120 - Variable speed control dial: Position 3

Continuous runtime



Test conditions: - Variable speed control dial: Position 3 - Grit of Abrasive paper disc: #120 - Battery: *BL1850B



High dust collection rate















198900-7(EU)

Wireless adapter set (WUT02) This adapter enables to use with supported AC vacuum cleaners equipped with auto start/ stop functions.



Cordless Drywall Sander DSL801 225 mm (8-7/8") Variable Speed Pad Diameter Abrasive Disc Size **Constant Speed** No Load Speed (RPM) Vibration Level Soft Start Sound Pressure Leve

Dimensions $(L \times W \times H)$ Net weight Kallection

210 mm (8-1/4") 225 mm (8-7/8") 1.000 - 1.800 Disc Sanding: 2.5 m/s² or less 75 dB(A) 1,120-1,540 x 278 x 273 mm (44"-60-1/2 x 11" x 10-3/4") 4.6 - 5.8 kg (10.1 - 12.8 lbs.)

Standard Equipment : Abrasive Disc, Hex Wrench, Tool Bag, Wireless Unit (country-specific), Front cuffs 24 (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. ms of stand cifications may vary by country or area.

H Hook & Loop

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan